

Stainless Steel Convoluted High Pressure Flexible Hose with FKM or EPDM Non-Return Valve





- Fitted Non-Return Valve (NRV)
- 1/4" NPT Female Inlet
- 1/4" NPT Male Outlet from NRV
- Anti-Whip & 90° Elbow (cylinder connection end)

MATERIAL

Convoluted Stainless Tube Hose

Stainless Steel ■ Fittings

The Chem Master SGF660 Series high pressure flexible hose assemblies are designed for use with corrosive, toxic and high purity gases up to grade 6.0 purity (99.9999%). They are intended for use in conjunction with our gas control panels.

- SGF661 | Stainless Steel Convoluted High Pressure Flexible Hose with FKM Non-Return Valve
- SGF662 | Stainless Steel Convoluted High Pressure Flexible Hose with EPDM Non-Return Valve

SPECIFICATION

300 bar (4350 PSI) Maximum Working Pressure

■ Temperature Range -40° C to +100° C (-5° F to +212° F)

■ Weight 1.0 kg (2.20 lb) 900 mm typical

Helium Leak Integrity 1x10⁻⁹ mbar I/s

12 MODEL NO. SELECTOR GUIDE

Example for a Model No. for SGF660 Series

SGF660-	04-	02-	01-	00-	000-	04-	Α
Product Type	Inlet Pressure Bar [PSI]	Length	Non Return Valve	Colour	Inlet/ Cylinder Connection	Outlet	Options
SGF661	04 300 [4350]	02 900 mm	01 NRV fitted	00 No option	000 1/4 NPT Female	04 1/4 NPT Male	A No Options Selected
SGF662		03 1800 mm			010 BS341 No.3		K Certificate of Conformity
					012 BS341 No.4		P Calibration / Pressure Test Certificate
					other connetions available, please refer to the data sheet "Cylinder connection"		



Headoffice / Factory UK

Gas-Arc Group Limited Vinces Road | Diss | Norfolk | IP22 4WW | UK t: +44 (0) 1379 652263 | f: +44 (0) 1379 644235 Office Germany

Aegidienstraße 12 | 23552 Lübeck | Germany t: +49 (0) 451 790 77 543